

SMART PDU HORIZONTAL 32A

Características:

- Indicador de estado LCD/RGB
- Módulo de toma de salida reemplazable
- Diseño de estructura compacta
- Controlador hot swap sin tornillos
- Monitoreo integral
- Opciones de instalación flexibles.
- Monitoreo vía Browser



Plug&Play | Seguro y confiable | Eficiencia Energética | Flexible



TELECOM



DATA
CENTER



EQUIPOS
MÉDICOS



SERVIDORES



MINERÍA



SEGURIDAD

ESPECIFICACIONES TÉCNICAS

CARACTERÍSTICAS	
SKU	EPDUM06021X
Input	
Nominal Voltage	230V
Frequency	50/60Hz
Phase	Sigle phase
Plug Type	IEC60309 (32A 230VAC 2P+N+E)
Power Cord Spec	3 x6mm² x 3 meters; Top Entry
Max Input Current	32A per phase
Rated Input Current	32A per phase
Wiring Style	L-N wiring
Power Capacity	7360W
Output	
Nominal Voltage	230V
Max Output Current	32A per phase
Output Connections	6 x IEC 320 C13 & 2 x IEC 320 C1 9
Outlet Locking	None
Protections	
Circuit Overload Protection	None
Surge Suppression	None
Metering	
Input/phase/circuit Metering	Yes
Breaker Status Monitoring	Yes
Metering Accuracy	+/- 1%
Environmental Monitoring	Temperature, Humidity
Monitoring Parameters	Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor
Communication	
Access	SNMP (V1, V2c, V3), HT TP/HTTPS , Telnet, Modbus-RTU
Authentication	N/A
Alerts	Voltage, current, (temperature, humidity) optional
Service	TFTP, SMTP
Daisy-chain	1 master 4 slaves
Physical	
Product Dimensions (HxWxD)	486*116*44.4mm
Box Dimensions (HxWx D)	TBD
Product Weight	TBD
Box Weight	TBD
Mounting Style	2 end Brackets
Mounting Distance	460mm
Environmental	
Operating Temperature	-10~45
Operating Relative Humidity	5%~95%
Operating Elevation	0~3000 meters
Compliance	
EMC Verification	EN55032, EN61000, EN55035



UPS



ESTABILIZADORES



SERVICIOS



BATERÍAS



DATACENTER



CLIMATIZACIÓN